

1800 NOFALL (1800 663 255)

1800 NOFALL (1800 663 255)

1800 NOFALL (1800 663 255)



FEATURES

- Plant registered for site use
- Completely Australian made and owned
- Quality manufactured safety product
- A safe alternative to ladders
- Takes minutes to assemble
- Is light weight
- Quick and easy to move
- Easy to store
- Optional powdercoat finish

TYPICAL USES

Great for those jobs both inside & out such as

- Building & home improvements
- Gardening/Pruning
- Painting
- Cleaning gutters
- Window cleaning
- Plumbing
- Trimming hedges
- Household maintenance
- Even hanging the Christmas decorations
- And many more jobs where you need work at height safety
- Optional stair kits and screw jacks for use on uneven surfaces and stairways



Please Note

- Never use during electrical work
- Never leave children unattended around an assembled model



Proudly manufactured by



Your Height and Customised Access Specialists

PHONE 1800 NOFALL (1800 663 255)

www.miniskaff.com.au

Distributor Details



Domestic and Light Trade Safety Platforms

- Satisfies Australian Standard 1576.1:2010 part 3
 - Design registration number SD-20111985-1
- Great for jobs around home or light trade use, painting, gutter cleaning, domestic renovation & gardening jobs. Eliminate the risk of serious injury from ladders.



1800 NOFALL (1800 663 255)


1800 NOFALL (1800 663 255)

1800 NOFALL (1800 663 255)

MINISKAFF

LIGHT, STRONG, SAFE & EASY

612 Assembly Instructions



1. Layout base plates with wheels facing outwards at rear.



2. Attach base frames to base plates as shown.



3. Fit diagonal brace as shown.



4. Attach 2 frames across base frames as shown.




5. Fit the 2 Grip Planks on top of the second frames.



6. Attach 2 more frames as shown.



7. Attach curved handrails with eyelets facing outwards.



8. Attach work tray, safety bars and ladder.

912 Assembly Instructions



1. Layout base plates with wheels facing outwards at rear.



2. Attach base frames to base plates as shown.




3. Fit diagonal brace as shown.



4. Attach 2 frames across base frames as shown.



5. Fit the 3 Grip Planks and attach 2 more frames.



6. Attach curved handrails with eyelets facing outwards.



7. Attach worktray and safety bar.



8. Attach ladder and removable mid-rails.


All models - 225kg Safe Working Load

- Where possible the construction of all models should be undertaken by at least two people in order to assemble safely.
- It is advisable to wear appropriate safety wear such as gloves and fully enclosed footwear
- Never climb on the outside of the towers unless using a ladder. Always climb inside the tower during construction and use.
- When moving a tower, always hold the base frame and the frame above, then tilt onto wheels.
(see picture right).
- Safety data sheet available from website



918 Assembly Instructions

Assemble the same as 912, up to step 5.




6. Attach 2 more frames and removable mid-rails.



7. Attach curved handrails, safety rails and work tray.



8. Connect and pin lower section of ladder.



9. Raise the 3 grip planks onto 3rd frame and hook on ladder.



Your Height and Customised Access Specialists

Phone 1800 NOFALL (1800 663 255)

www.miniskaff.com.au